

Page 1 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.02.2017 / 0001 Replacing version dated / version: 14.02.2017 / 0001 Valid from: 14.02.2017 PDF print date: 14.02.2017 Top Tec 6100 0W-30 5 L Art.: 20779

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

# **1.1 Product identifier**

Top Tec 6100 0W-30 5 L Art.: 20779

# **1.2** Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Motor oil Sector of use [SU]:

അ

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU21 - Consumer uses: Private households (=general public = consumers) SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Chemical product category [PC]: PC17 - Hydraulic fluids PC24 - Lubricants, greases, release products Process category [PROC]: PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC20 - Use of functional fluids in small devices Article Categories [AC]: AC99 - Not required. Environmental Release Category [ERC]: ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 7 - Use of functional fluid at industrial site ERC 9a - Widespread use of functional fluid (indoor) ERC 9b - Widespread use of functional fluid (outdoor) Uses advised against: No information available at present. 1.3 Details of the supplier of the safety data sheet GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

# 1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture



Page 2 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.02.2017 / 0001 Replacing version dated / version: 14.02.2017 / 0001 Valid from: 14.02.2017 PDF print date: 14.02.2017 Top Tec 6100 0W-30 5 L Art.: 20779

# Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

### 2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains C14-16-18 Alkylphenol. May produce an allergic reaction. EUH210-Safety data sheet available on request.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %). The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

# **SECTION 3: Composition/information on ingredients**

#### 3.1 Substance

#### n.a. 3.2 Mixture

_3.2 Mixture	
Distillates (petroleum), hydrotreated heavy paraffinic	
Registration number (REACH)	01-2119484627-25-XXXX
Index	649-467-00-8
EINECS, ELINCS, NLP	265-157-1
CAS	64742-54-7
content %	60-80
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	
Registration number (REACH)	01-2119474889-13-XXXX
Index	649-483-00-5
EINECS, ELINCS, NLP	276-738-4
CAS	72623-87-1
content %	1-2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	
Registration number (REACH)	01-2119474878-16-XXXX
Index	649-482-00-X
EINECS, ELINCS, NLP	276-737-9
CAS	72623-86-0
content %	1-2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures Inhalation Supply person with fresh air and consult doctor accord

Supply person with fresh air and consult doctor according to symptoms.

Skin contact



Page 3 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.02.2017 / 0001 Replacing version dated / version: 14.02.2017 / 0001 Valid from: 14.02.2017 PDF print date: 14.02.2017 Top Tec 6100 0W-30 5 L Art.: 20779

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

# Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

ആ

Rinse the mouth thoroughly with water. Do not induce vomiting. Consult doctor immediately.

# 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. Irritation of the eyes Irritation of the skin. Allergic reaction

# 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

#### Suitable extinguishing media

CO2 Foam Dry extinguisher Water mist

#### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Toxic gases

# 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

**SECTION 6:** Accidental release measures

# 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air. Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

### 6.2 Environmental precautions

#### If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Fill the absorbed material into lockable containers.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

**SECTION 7: Handling and storage** 



Page 4 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.02.2017 / 0001 Replacing version dated / version: 14.02.2017 / 0001 Valid from: 14.02.2017 PDF print date: 14.02.2017 Top Tec 6100 0W-30 5 L Art.: 20779

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

# 7.1 Precautions for safe handling

# 7.1.1 General recommendations

Ensure good ventilation. Avoid formation of oil mist. Avoid contact with eyes or skin. Do not carry cleaning cloths soaked in product in trouser pockets. Do not heat to temperatures close to flash point. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Under all circumstances prevent penetration into the soil. Store at room temperature.

Store in a dry place.

#### 7.3 Specific end use(s)

No information available at present.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)	
Monitoring procedures:	<ul> <li>Draeger - Oil 10/a-P (67 28 371)</li> </ul>	
	- Draeger - Oil Mist 1/a (67 33 031)	
BMGV:	Other information:	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Distillates (petroleum), hydro	Distillates (petroleum), hydrotreated heavy paraffinic										
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note					
	Environmental		-								
	compartment										
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3	24h					
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m3	8h					

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based											
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note					
	Environmental										
	compartment										
	Human - oral		PNEC	9,33	mg/kg feed						
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3	24h					
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m3	8h					



Page 5 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.02.2017 / 0001 Replacing version dated / version: 14.02.2017 / 0001 Valid from: 14.02.2017 PDF print date: 14.02.2017 Top Tec 6100 0W-30 5 L Art.: 20779

Lubricating oils (petroleum),	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based										
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note					
	Environmental										
	compartment										
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3	24h					
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,4	mg/m3	8h					

### 8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

ആ

Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection - Hand protection: Protective gloves, oil resistant (EN 374) Recommended Protective nitrile gloves (EN 374) Minimum layer thickness in mm: >= 0,38 Permeation time (penetration time) in minutes: >= 480 Protective hand cream recommended. The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. With oil mist formation: Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.



Page 6 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.02.2017 / 0001 Replacing version dated / version: 14.02.2017 / 0001 Valid from: 14.02.2017 PDF print date: 14.02.2017 Top Tec 6100 0W-30 5 L Art.: 20779

#### 8.2.3 Environmental exposure controls

No information available at present.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state: Colour: Odour: Odour threshold: pH-value: Melting point/freezing point: Initial boiling point and boiling range: Flash point: Evaporation rate: Flammability (solid, gas): Lower explosive limit: Upper explosive limit: Vapour pressure: Vapour density (air = 1): Density: Bulk density: Solubility(ies): Water solubility: Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Viscosity: Explosive properties: Oxidising properties: 9.2 Other information

Miscibility: Fat solubility / solvent: Conductivity: Surface tension: Solvents content:

Liquid Brown Characteristic Not determined Not determined Not determined Not determined 228 °C Not determined n.a. Not determined Not determined Not determined Not determined 0,841 g/ml n.a. Not determined Insoluble Not determined Not determined Not determined 53,3 mm2/s (40°C) 9,9 mm2/s (100°C) Product is not explosive. No Not determined

Not determined Not determined Not determined Not determined

#### SECTION 10: Stability and reactivity

#### **10.1 Reactivity**

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** Strong heat **10.5 Incompatible materials** 

Avoid contact with strong oxidizing agents. Avoid contact with strong alkalis. Avoid contact with strong acids.

# 10.6 Hazardous decomposition products

No decomposition when used as directed.

#### **SECTION 11: Toxicological information**



œ Page 7 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.02.2017 / 0001 Replacing version dated / version: 14.02.2017 / 0001 Valid from: 14.02.2017 PDF print date: 14.02.2017 Top Tec 6100 0W-30 5 L Art.: 20779

**11.1 Information on toxicological effects** Possibly more information on health effects, see Section 2.1 (classification). **Top Tec 6100 0W-30 5 L** 

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Distillates (petroleum), hydrotr	eated heavy p	oaraffinic				
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral	
					toxicity - Fixe Dose	
					Procedure)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	5,53	mg/l/4h	Rat	OECD 403 (Acute	Aerosol
					Inhalation Toxicity)	
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Slightly irritant
Respiratory or skin						Not sensitizising
sensitisation:						
Aspiration hazard:						Yes

Lubricating oils (petroleum), C	20-50, hydrotr	reated neutral	l oil-based			
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant,
					Dermal	Repeated
					Irritation/Corrosion)	exposure may
						cause skin
						dryness or
						cracking.
Serious eye damage/irritation:					OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin					OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Carcinogenicity:					OECD 451	Negative
					(Carcinogenicity Studies)	



Page 8 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.02.2017 / 0001 Replacing version dated / version: 14.02.2017 / 0001 Valid from: 14.02.2017 PDF print date: 14.02.2017 Top Tec 6100 0W-30 5 L Art.: 20779

œ

OECD 453 (Combined Carcinogenicity: Negative Chronic Toxicity/Carcinogenicity Studies) Reproductive toxicity: OECD 414 (Prenatal Negative **Developmental Toxicity** Study) Reproductive toxicity: OECD 421 Negative (Reproduction/Developm ental Toxicity Screening Test) Aspiration hazard: Asp. Tox. 1

_ubricating oils (petroleum), C	15-30, nyaroti					1
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/m3/4h	Rat	OECD 403 (Acute	Aerosol
			-		Inhalation Toxicity)	
Aspiration hazard:						Yes
Symptoms:						nausea and
						vomiting.

# **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification). Top Tec 6100 0W-30 5 L Art.: 20779 Value Toxicity / effect Endpoint Time Unit Organism Test method Notes 12.1. Toxicity to fish: 12.1. Toxicity to daphnia: n.d.a. n.d.a. 12.1. Toxicity to algae: n.d.a. 12.2. Persistence and n.d.a. degradability: 12.3. Bioaccumulative n.d.a. potential: 12.4. Mobility in soil: n.d.a. 12.5. Results of PBT n.d.a. and vPvB assessment 12.6. Other adverse n.d.a. effects:

Foxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	28d	>1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	48h	>100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	



Page 9 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.02.2017 / 0001 Replacing version dated / version: 14.02.2017 / 0001 Valid from: 14.02.2017 PDF print date: 14.02.2017 Top Tec 6100 0W-30 5 L Art.: 20779

œ.

12.2. Persistence and degradability:		28d	6	%	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
Other information:	AOX		0	%		

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	96h	>=100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity	
12.1. Toxicity to fish:	LL50	96h	> 100	mg/l	Pimephales promelas	Test) OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EL50	48h	>100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	46	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.3. Bioaccumulative potential:	Log Kow		4,1				A notable biological accumulation potential has to be expected (LogPow > 3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	NOEC/NOEL	10min	>1,93	mg/l		DIN 38412 T.8	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	14d	>=1000	mg/l	Oncorhynchus mykiss	QSÁR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l			
12.3. Bioaccumulative potential:							Readily biodegradable



Page 10 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.02.2017 / 0001 Replacing version dated / version: 14.02.2017 / 0001

œ

Replacing version dated / version: 14.02.2017 / 0001 Valid from: 14.02.2017 PDF print date: 14.02.2017 Top Tec 6100 0W-30 5 L Art.: 20779

Log Pow

Other information:

# SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

6,1

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Observe regulations for disposal of old oil/waste.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

#### SECTION 14: Transport information

4.1. UN number:	n.a.
Fransport by road/by rail (ADR/RID)	
4.2. UN proper shipping name:	
4.3. Transport hazard class(es):	n.a.
4.4. Packing group:	n.a.
Classification code:	n.a.
Q:	n.a.
4.5. Environmental hazards:	Not applicable
unnel restriction code:	
Fransport by sea (IMDG-code)	
4.2. UN proper shipping name:	
4.3. Transport hazard class(es):	n.a.
4.4. Packing group:	n.a.
larine Pollutant:	n.a
4.5. Environmental hazards:	Not applicable
Fransport by air (IATA)	
4.2. UN proper shipping name:	
4.3. Transport hazard class(es):	n.a.
4.4. Packing group:	n.a.
4.5. Environmental hazards:	Not applicable
4.6. Special precautions for user	

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

# **SECTION 15: Regulatory information**

#### **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.



Page 11 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.02.2017 / 0001 Replacing version dated / version: 14.02.2017 / 0001 Valid from: 14.02.2017 PDF print date: 14.02.2017 Top Tec 6100 0W-30 5 L Art.: 20779

Directive 2010/75/EU (VOC):

1,8 %

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

# **SECTION 16: Other information**

Revised sections:

GB

n.a.

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

Asp. Tox. — Aspiration hazard

#### Any abbreviations and acronyms used in this document:

AC Article Categories
acc., acc. to according, according to
ACGIH American Conference of Governmental Industrial Hygienists
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the
International Carriage of Dangerous Goods by Road)
AOEL Acceptable Operator Exposure Level
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
BMGV Biological monitoring guidance value (EH40, UK)
BOD Biochemical oxygen demand
BSEF Bromine Science and Environmental Forum
bw body weight
CAS Chemical Abstracts Service
CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
CIPAC Collaborative International Pesticides Analytical Council
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances
and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
COD Chemical oxygen demand
CTFA Cosmetic, Toiletry, and Fragrance Association
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
DT50 Dwell Time - 50% reduction of start concentration
DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community



ആ Page 12 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.02.2017 / 0001 Replacing version dated / version: 14.02.2017 / 0001 Valid from: 14.02.2017 PDF print date: 14.02.2017 Top Tec 6100 0W-30 5 L Art.: 20779 EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances FN European Norms EPA United States Environmental Protection Agency (United States of America) ERC **Environmental Release Categories** ES Exposure scenario etc. et cetera European Union FU EWC European Waste Catalogue Fax number Fax. gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential HET-CAM Hen's Egg Test - Chorionallantoic Membrane HGWP Halocarbon Global Warming Potential International Agency for Research on Cancer IARC International Air Transport Association IATA Intermediate Bulk Container IBC IBC (Code) International Bulk Chemical (Code) Inhibitory concentration IC IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform ChemicaL Information Database lethal concentration I C lethal concentration 50 percent kill LC50 LCLo lowest published lethal concentration Lethal Dose of a chemical LD LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available NIOSH National Institute of Occupational Safety and Health (United States of America) NOAECNo Observed Adverse Effective Concentration NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level **Ozone Depletion Potential** ODP OECD Organisation for Economic Co-operation and Development organic org. PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic PC Chemical product category PE Polyethylene PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential parts per million ppm PROC Process category PTFE Polytetrafluorethylene REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) **REACH-IT List-No.** 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SADT Self-Accelerating Decomposition Temperature Structure Activity Relationship SAR



Page 13 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 14.02.2017 / 0001 Replacing version dated / version: 14.02.2017 / 0001 Valid from: 14.02.2017 PDF print date: 14.02.2017 Top Tec 6100 0W-30 5 L Art.: 20779 SU Sector of use SVHC Substances of Very High Concern Tel. Telephone ThOD Theoretical oxygen demand TOC Total organic carbon TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VbF VOC Volatile organic compounds vPvB very persistent and very bioaccumulative WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK). WHO World Health Organization wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility. These statements were made by:

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax:

### +49 5233 94 17 90

GB

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.