

Page 1 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.06.2019 / 0023 Replacing version dated / version: 09.07.2018 / 0022 Valid from: 18.06.2019 PDF print date: 18.06.2019 ProLine Benzin System Reiniger 500 mL Art.: 5153

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

(GB)

ProLine Benzin System Reiniger 500 mL Art.: 5153

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Additives Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet (B)

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixtureClassification according to Regulation (EC) 1272/2008 (CLP)Hazard classHazard categoryHazard statementAsp. Tox.1H304-May be fatalAquatic Chronic3H412-Harmful to act

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)





Page 2 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.06.2019 / 0023 Replacing version dated / version: 09.07.2018 / 0022 Valid from: 18.06.2019 PDF print date: 18.06.2019 ProLine Benzin System Reiniger 500 mL Art.: 5153

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P301+P310+P331-IF SWALLOWED: Immediately call a POISON CENTER / doctor. Do NOT induce vomiting. P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics Hydrocarbons, C10, aromatics, >1% naphthalene

2.3 Other hazards

ആ

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0, 1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	
EINECS, ELINCS, NLP	918-481-9 (REACH-IT List-No.)
CAS	
content %	60-90
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
Hydrocarbons, C10, aromatics, >1% naphthalene	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	919-284-0 (REACH-IT List-No.)
CAS	(64742-94-5)
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
	STOT SE 3, H336
	Aquatic Chronic 2, H411
Naphthalene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	601-052-00-2
EINECS, ELINCS, NLP	202-049-5
CAS	91-20-3
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Carc. 2, H351
	Acute Tox. 4, H302
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.



Page 3 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.06.2019 / 0023 Replacing version dated / version: 09.07.2018 / 0022 Valid from: 18.06.2019 PDF print date: 18.06.2019 ProLine Benzin System Reiniger 500 mL Art.: 5153

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7).

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

അ

Remove person from danger area. Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Wash thoroughly with soap and water - consult doctor if necessary.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately. Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam Extinction powder Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of nitrogen Toxic gases

Flammable vapour/air mixtures

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep unprotected persons away.



Page 4 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.06.2019 / 0023 Replacing version dated / version: 09.07.2018 / 0022 Valid from: 18.06.2019 PDF print date: 18.06.2019 ProLine Benzin System Reiniger 500 mL Art.: 5153

Remove possible causes of ignition - do not smoke. Ensure sufficient supply of air. Avoid inhalation, and contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

ആ

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke. Take precautions against electrostatic charges. Avoid contact with eyes or skin. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing. Not to be stored in gangways or stair wells. Observe special storage conditions. Solvent resistant floor Do not store with oxidizing agents.

Store in a well ventilated place. Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Content %:60-90				
WEL-TWA: 800 mg/m3	WEL-STEL:					
Monitoring procedures:	- Draeger - Hydrocarbons 2/a (81 03 581)					
	 Draeger - Hydrocarbons 0,1%/c (81 03 571) 					
	- Compur - KITA-187 S (551 174)					
BMGV:	Other information: (C	DEL acc. to RCP-method,				
	paragraphs 84-87, EH40)					



Page 5 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.06.2019 / 0023 Replacing version dated / version: 09.07.2018 / 0022 Valid from: 18.06.2019 PDF print date: 18.06.2019 ProLine Benzin System Reiniger 500 mL Art.: 5153

ആ

Chemical Name	Hydrocarbons, C10	0, aromatics, >1% naphthalene		Content %:1-5
WEL-TWA: 500 mg/m3 (Aromatics	5)	WEL-STEL:		
Monitoring procedures:	- [Draeger - Hydrocarbons 2/a (81 03	581)	
	- [Draeger - Hydrocarbons 0,1%/c (81	03 571)	
	- (Compur - KITA-187 S (551 174)		
BMGV:			Other information:	
Chemical Name	Naphthalene			Content %:0,1-<1
WEL-TWA: 500 mg/m3 (Aromatics) (WEL), 10 ppm	WEL-STEL:		
(50 mg/m3) (EU)				
Monitoring procedures:	- (Compur - KITA-153 U(C) (551 182)	1	
BMGV:			Other information:	
Chemical Name	Hydrocarbons, C1	1-C14, n-alkanes, isoalkanes, cycli	cs, <2% aromatics	Content %:
WEL-TWA: 1200 mg/m3 (>=C7 no	rmal and branched	WEL-STEL:		
chain alkanes)				
Monitoring procedures:		Draeger - Hydrocarbons 2/a (81 03		
	- [Draeger - Hydrocarbons 0,1%/c (81	03 571)	
	- (Compur - KITA-187 S (551 174)		
BMGV:			Other information:	

Naphthalene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	2,4	µg/l	
	Environment - marine		PNEC	0,24	µg/l	
	Environment - sewage treatment plant		PNEC	2,9	mg/l	
	Environment - sediment, freshwater		PNEC	0,0672	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,0672	mg/kg dry weight	
	Environment - soil		PNEC	0,0533	mg/kg dry weight	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	3,57	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	25	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	25	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".



Page 6 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.06.2019 / 0023 Replacing version dated / version: 09.07.2018 / 0022 Valid from: 18.06.2019 PDF print date: 18.06.2019 ProLine Benzin System Reiniger 500 mL Art.: 5153

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

ആ

Skin protection - Hand protection: Solvent resistant protective gloves (EN 374). If applicable Protective Viton® / fluoroelastomer gloves (EN 374) Permeation time (penetration time) in minutes: > 480 Minimum layer thickness in mm: > 0,4 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown At high concentrations: Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138) Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Light yellow
Colour:	Clear
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	>63 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined



Page 7 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.06.2019 / 0023 Replacing version dated / version: 09.07.2018 / 0022 Valid from: 18.06.2019 PDF print date: 18.06.2019 ProLine Benzin System Reiniger 500 mL Art.: 5153

Upper explosive limit: Vapour pressure: Vapour density (air = 1): Density: Bulk density: Solubility(ies): Water solubility: Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Explosive properties: Oxidising properties:

9.2 Other information

Miscibility: Fat solubility / solvent: Conductivity: Surface tension: Solvents content:

œ

Not determined Not determined Not determined 0,820 g/ml (15°C) Not determined Insoluble Not determined Not determined Not determined <7 mm2/s (40°C) Not determined No

Not determined Not determined Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources Electrostatic charge

10.5 Incompatible materials

Avoid contact with strong oxidizing agents. Avoid contact with strong acids.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on hea	alth effects, see	e Section 2.1 (classification).			
ProLine Benzin System Reinig	er 500 mL		· · ·			
Art.: 5153						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.



Page 8 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.06.2019 / 0023 Replacing version dated / version: 09.07.2018 / 0022 Valid from: 18.06.2019 PDF print date: 18.06.2019 ProLine Benzin System Reiniger 500 mL Art.: 5153

œ

Carcinogenicity:			negative, the
			real
			Naphthalene
		 	content is <1%
Reproductive toxicity:			n.d.a.
Specific target organ toxicity -			n.d.a.
single exposure (STOT-SE):			
Specific target organ toxicity -			n.d.a.
repeated exposure (STOT-RE):			
Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.

Hydrocarbons, C10-C13, n-alka Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	Analogous
					Dermal Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	>4951	mg/m3/4h	Rat	OECD 403 (Acute	Analogous
					Inhalation Toxicity)	conclusion,
						Vapours
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye	Not irritant.
conodo ofo damago, manom					Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin					OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	Analogous
					Centrational	conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative,
Control matagementy.					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	conclusion
Germ cell mutagenicity:					OECD 474 (Mammalian	Negative,
Control matagementy.					Erythrocyte	Analogous
					Micronucleus Test)	conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
Cerm cen matagementy.				typhimurium	Reverse Mutation Test)	Negative
Carcinogenicity:				typrinnanann	OECD 453 (Combined	Negative,
Careinogerneity.					Chronic	Analogous
					Toxicity/Carcinogenicity	conclusion
					Studies)	Conclusion
Reproductive toxicity:					OECD 414 (Prenatal	Negative,
Reproductive toxicity.					Developmental Toxicity	Analogous
					Study)	conclusion
Specific target organ toxicity -					OECD 408 (Repeated	Negative,
repeated exposure (STOT-RE):					Dose 90-Day Oral	Analogous
					Toxicity Study in	conclusion
					Rodents)	Controlasion
Aspiration hazard:						Yes
Symptoms:						unconsciousnes
cymptonio.						, headaches,
						dizziness
Other information:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.
				l		l clacking.
Hydrocarbons, C10, aromatics,					1	1
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes



Page 9 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.06.2019 / 0023 Replacing version dated / version: 09.07.2018 / 0022 Valid from: 18.06.2019 PDF print date: 18.06.2019 ProLine Benzin System Reiniger 500 mL Art.: 5153

œ)

Acute toxicity, by oral route:	LD50	~7093	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4688	mg/m3	Rat	OECD 403 (Acute	
			-		Inhalation Toxicity)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	

Hydrocarbons, C11-C14, n-alka Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	110103
Acute toxicity, by oral route.	LD30	25000	iiig/kg	Παι	Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
Acute toxicity, by definial route.	LDSU	20000	iiig/kg	πασοπ	Dermal Toxicity)	
Skin corrosion/irritation:					Dennai Toxicity)	Repeated
Skin conosion/initiation.						exposure may
						cause skin
						dryness or
Olivia a suma sis a finaita ti sus						cracking.
Skin corrosion/irritation:					OECD 404 (Acute	Analogous
					Dermal	conclusion,
					Irritation/Corrosion)	Drying of the
						skin., Dermatitis
						(skin
						inflammation)
Serious eye damage/irritation:					OECD 405 (Acute Eye	Analogous
					Irritation/Corrosion)	conclusion,
						Slightly irritant
Respiratory or skin				Rat		Not sensitizising
sensitisation:						
Germ cell mutagenicity:				Salmonella	in vivo	Negative
				typhimurium		
Carcinogenicity:					OECD 453 (Combined	Analogous
					Chronic	conclusion,
					Toxicity/Carcinogenicity	Negative
					Studies)	- J
Reproductive toxicity:					OECD 414 (Prenatal	Analogous
1					Developmental Toxicity	conclusion,
					Study)	Negative
Specific target organ toxicity -						Analogous
single exposure (STOT-SE):						conclusion, No
						indications of
						such an effect.
Specific target organ toxicity -					OECD 408 (Repeated	Analogous
repeated exposure (STOT-RE):					Dose 90-Day Oral	conclusion, Not
repeated exposure (0101-RE).					Toxicity Study in	to be expected
					Rodents)	
Aspiration hazard:	+					Yes
Symptoms:	+					drying of the
Symptoms.						skin.,
						headaches,
						fatigue,
						dizziness,
						nausea,
						diarrhoea,
						vomiting

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).



- (GB)							
Page 10 of 14							
Safety data sheet accordir			07/2006, Ar	inex II			
Revision date / version: 18		•					
Replacing version dated /	version: 09.07.2	2018 / 0022					
Valid from: 18.06.2019							
PDF print date: 18.06.201							
ProLine Benzin System Re	einiger 500 mL						
Art.: 5153							
ProLine Benzin System	Reiniger 500 m	L					
Art.: 5153							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							Isolate as much
degradability:							as possible with
							an oil separator.
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							
Other information:							According to the
							recipe, contains
							no AOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT	-						No PBT
and vPvB assessment							substance, No
							vPvB substance
Water solubility:							Product floats o
-							the water
							surface.
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus	OECD 203 (Fish,	
-					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to fish:	NOELR	28d	0,101	mg/l	Oncorhynchus	,	
					mykiss		
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,176	mg/l	Daphnia magna		
12.2. Persistence and		28d	80	%	activated sludge	OECD 301 F	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Manometric	
						Respirometry Test)	
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
				-	a subcapitata	Growth Inhibition	
						Test)	
Other organisms:	EL50	48h	>1000	mg/l	Tetrahymen		
-				-	pyriformis		

Hydrocarbons, C10, aromatics, >1% naphthalene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	EL50	48h	10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	72h	>1-<3	mg/l	Raphidocelis subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes



Page 11 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.06.2019 / 0023 Replacing version dated / version: 09.07.2018 / 0022 Valid from: 18.06.2019 PDF print date: 18.06.2019 ProLine Benzin System Reiniger 500 mL Art.: 5153

12.1. Toxicity to fish:	NOELR	28d	0,17	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOELR	21d	1,22	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
				_	a subcapitata	Growth Inhibition	
						Test)	
12.2. Persistence and		28d	69	%		OECD 301 F	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Manometric	
						Respirometry Test)	
12.3. Bioaccumulative	Log Pow		6-8				High
potential:							
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no.:

œ

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

14 06 03 other solvents and solvent mixtures

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements 14.1. UN number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.



Page 12 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.06.2019 / 0023 Replacing version dated / version: 09.07.2018 / 0022 Valid from: 18.06.2019 PDF print date: 18.06.2019 ProLine Benzin System Reiniger 500 mL Art.: 5153

14.4. Packing group:14.5. Environmental hazards:

ആ

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

n.a.

Not applicable

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

2.15

Revised sections:

These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard Aquatic Chronic — Hazardous to the aquatic environment - chronic STOT SE — Specific target organ toxicity - single exposure - narcotic effects Carc. — Carcinogenicity Acute Tox. — Acute toxicity - oral Aquatic Acute — Hazardous to the aquatic environment - acute

Any abbreviations and acronyms used in this document:

99,64 %



Page 13 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.06.2019 / 0023 Replacing version dated / version: 09.07.2018 / 0022 Valid from: 18.06.2019 PDF print date: 18.06.2019 ProLine Benzin System Reiniger 500 mL Art.: 5153 acc., acc. to according, according to ACGIH American Conference of Governmental Industrial Hygienists ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) BGV BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK) BOD Biochemical oxygen demand BSEF Bromine Science and Environmental Forum bw body weight CAS Chemical Abstracts Service Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CEC CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques CIPAC Collaborative International Pesticides Analytical Council Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances CLP and mixtures) CMR carcinogenic, mutagenic, reproductive toxic COD Chemical oxygen demand CTFA Cosmetic, Toiletry, and Fragrance Association DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon DT50 Dwell Time - 50% reduction of start concentration Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) DVS dw dry weight e.g. for example (abbreviation of Latin 'exempli gratia'), for instance European Community EC ECHA European Chemicals Agency European Economic Area FFA EEC European Economic Community European Inventory of Existing Commercial Chemical Substances EINECS ELINCS European List of Notified Chemical Substances ΕN **European Norms** EPA United States Environmental Protection Agency (United States of America) ERC **Environmental Release Categories** ES Exposure scenario etc. et cetera EU European Union EWC European Waste Catalogue Fax. Fax number general gen. GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Hen's Egg Test - Chorionallantoic Membrane HET-CAM HGWP Halocarbon Global Warming Potential IARC International Agency for Research on Cancer IATA International Air Transport Association IBC Intermediate Bulk Container IBC (Code) International Bulk Chemical (Code) IC Inhibitory concentration IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive **IUCLID** International Uniform ChemicaL Information Database lethal concentration LC lethal concentration 50 percent kill LC50

ആ



ആ Page 14 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.06.2019 / 0023 Replacing version dated / version: 09.07.2018 / 0022 Valid from: 18.06.2019 PDF print date: 18.06.2019 ProLine Benzin System Reiniger 500 mL Art.: 5153 lowest published lethal concentration LCLo LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level Limited Quantities 10 MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available NIOSH National Institute of Occupational Safety and Health (United States of America) NOAECNo Observed Adverse Effective Concentration NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level ODP **Ozone Depletion Potential** OECD Organisation for Economic Co-operation and Development organic org. PAH polycyclic aromatic hydrocarbon persistent, bioaccumulative and toxic PBT PC Chemical product category PF Polyethylene PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential ppm parts per million PROC Process category PTFE Polytetrafluorethylene REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SADT Self-Accelerating Decomposition Temperature SAR Structure Activity Relationship SU Sector of use SVHC Substances of Very High Concern Telephone Tel. ThOD Theoretical oxygen demand TOC Total organic carbon TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VbF VOC Volatile organic compounds vPvB very persistent and very bioaccumulative WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) WEL-TWA, WEL-STEL reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK). WHO World Health Organization wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.